









EOR-IOR APPLICATIONS IN MOL'S PRACTICE

János Szelényi

Production Technology Advisor MOL Group Reservoir Engineering

Islamabad, Pakistan 7 May 2015

DISCLAIMER

This presentation and the associated slides and discussion contain forward-looking statements. These statements are naturally subject to uncertainty and changes in circumstances. Those forward-looking statements may include, but are not limited to, those regarding capital employed, capital expenditure, cash flows, costs, savings, debt, demand, depreciation, disposals, dividends, earnings, efficiency, gearing, growth, improvements, investments, margins, performance, prices, production, productivity, profits, reserves, returns, sales, share buy backs, special and exceptional items, strategy, synergies, tax rates, trends, value, volumes, and the effects of MOL merger and acquisition activities. These forward-looking statements are subject to risks, uncertainties and other factors, which could cause actual results to differ materially from those expressed or implied by these forward-looking statements. These risks, uncertainties and other factors include, but are not limited to developments in government regulations, foreign exchange rates, crude oil and gas prices, crack spreads, political stability, economic growth and the completion of ongoing transactions. Many of these factors are beyond the Company's ability to control or predict. Given these and other uncertainties, you are cautioned not to place undue reliance on any of the forward-looking statements contained herein or otherwise. The Company does not undertake any obligation to release publicly any revisions to these forward-looking statements (which speak only as of the date hereof) to reflect events or circumstances after the date hereof or to reflect the occurrence of unanticipated events, except as maybe required under applicable securities laws.

Statements and data contained in this presentation and the associated slides and discussions, which relate to the performance of MOL in this and future years, represent plans, targets or projections.



Contents

1. Oil and gas in Hungary












ABOUT MOL GROUP

MOLGROUP


is a leading international, integrated oil and gas company from Hungary, the heart of Europe, with over 75 years' experience and a proven track record.

In addition to the company's strong refinery and commercial position in the CEE region, increasing focus is now being given to its exploration and production assets where MOL Group has over two decades of presence.

OWNERSHIP STRUCTURE 2014



- Hungarian State
- CEZ MH B.V.
- OmanOil (Bp) Limited
- OTP Bank Plc.
- Magnolia Finance Limited
- ING Bank N.V.
- Other investors



CORE ACTIVITIES





ABOUT MOL GROUP

▶ 40 COUNTRIES

of operations in Europe, Middle-East, Africa and Asia

▶ 38 MILLION BARRELS

of oil-equivalent Hydrocarbons are produced annually which could fill a tanker train 1206 km long

► AROUND 29.000 EMPLOYEES

worldwide

Members of MOL Group











Strategic members of MOL Group










ABOUT MOL GROUP

MOL GROUP DOWNSTREAM

MOL Group Downstream operations:

- 6 production units
- ► Total capacity of 20.9 mtpa refining and 2.1 mtpa petrochemicals
- 1734 service stations
- 8 brands
- Presence in 11 CEE countries
- All operations are supported by a far-reaching logistics system and driven by Supply Chain Management.




ABOUT MOL GROUP MOL GROUP UPSTREAM

MOL Group Upstream operations:


- **Exploration** 13 assets countries
- Producing assets in 8 countries
- Strong presence in the CEE region with excellent cash-flow generation
- Diversified portfolio: Middle-East, Africa, CIS, Pakistan, North Sea




History of the Hungarian Petroleum Industry




Hungary is a mature ground for HC exploration and production












The Hungarian ,Playground'



Contents



2. Portfolio management and screening











Keeping or selling?

What is the concept of handling the production portfolio? Main questions:

From cradle to grave? Playing the whole story and squeeze out the last HC molecule?



If we decide to expand the life of the fields... Cyclic Screening Process



Focus on RF improvement – EOR Team from 2013

- regular screening of MOL Group producing or non-producing field portfolio for possible <u>EOR/IOR</u> and <u>EGR/IGR</u> applications,
- generating EOR/IOR and EGR/IGR projects,
- accelerating implementation of projects,
- project surveillance and analysis of results,
- harmonizing EOR/IOR related R&D
 projects with EOR/IOR strategy and
 support/accelerate their implementation,
- generating new EOR/IOR related R&D projects,
- supporting lobby activity with government offices (more incentive regulations regarding EOR/EGR).





Old screening results and new revision in 2013

Screening of Hungarian
 7 EOR project
 4 EGR project
 5 IOR project
 3 IGR project
 on the basis of NPV and



Fields for EOR projects	Proposed technology	Probability of	
		success	
Öttömös-East	Secondary gas cap (CO2/N2)	>50	ed as
Ásotthalom	Secondary gas cap (CO2/N2)	>50	ed as on
Sávoly-SE Triassic oil reservoirs	Secondary gas cap (CO2/N2)	>50	partly
Kiskundorozsma	Secondary gas cap (CO2/N2)	>50	
Budafa (Zala-Kerettye)	CO2 flooding	?	
Nagylengyel, Barabássz., Ortah., Pusztaap.	Secondary gas cap (CO2)	?	
Budafa (Budafa-3 East)	Gasoline + CO2 flooding	?	
Fields for EGR projects	Proposed technology	Probability of success	d
Pusztaföldvár Felső A-3	HC gas exchanging with CO2	>80	bared
Üllés (Miocene reservoir)	HC gas exchanging with CO2	>50	ared
Őriszentpéter-S gas condensate	HC gas recycling	?	
Szank (Miocene reservoir)	HC gas exchanging with CO2	?	ning
Potential increme	Drilling of 1 now wall	Consolled	ning :e



Contents





3. 40 years EOR experience









MOL has serious experience in IOR/EOR applications

IOR Applications

- ► Two sided / simultaneous water injection (GOC and WOC)
- Multifunctional application of horizontal well technology
- ► In-fill drillings
- ► Conformance control in oil and gas wells
- Fracturing in low perm reservoirs





EOR Applications


- ► CO₂ flooding in carbonate and sandstone reservoirs (Nagylengyel, Szank oil fields)
- ► CO₂ flooding combined with water injection in sandstone reservoirs (Budafa, Lovászi, Pusztaföldvár fields)
- Methane injection into an extra light oil reservoir (Algyő field, Tisza-1 reservoir)
- ► Ethane rich gas injection into a light oil reservoir (Algyő field, Tisza-2 reservoir)
- Nitrogen injection into a fractured metamorphic type oil reservoir (experimental, Kiskundorozsma field)
- ► Thermal methods (In-situ combustion, steam injection) in Demjén oil field
- ► Microbiological EOR in Demjén oil field

Results of EOR


- ► EOR production in 2014:
 - 62 084 t equal 11.2% of total Hungarian oil production
- ► EOR applications in Hungary resulted near to 5 million tons of oil from the beginning (from 1969)



CO₂ injection - the most frequent EOR application



CO₂ injection in Nagylengyel carbonate field



Components of success

- Understanding the Karst System and Primary recovery (long production history, water influx)
- Natural CO₂ resource in the vicinity of the field
- Reservoir management (monitoring oil front movement)
- High standard laboratory experiments and exploitation plans


Challenge

- Old wells, well integrity problems
- ► High H₂S content of the injected gas
- **▶** Corrosion
- Complex reservoir properties (karstic carbonate reservoir)
- ► Environmental concerns (CO₂ disposal after depletion of the field)


Solution

- ▶ Pilot testing
- ► New CO₂ well design
- ► Treatment CO₂ disposal
- H₂S and corrosion handling
- ► Field trials in two phases (Third phase of the project is under preparation now)

Temperature	C°	114
Initial pressure	bar	207
Porosity	%	1.2
Permeability	D	3.8
Oil Viscosity	mPas	19




Phases of artificial CO₂ gas cap EOR process






CO₂ flooding in Nagylengyel field – results and extension

Moving of gas fluid contact during injection




Tendency of oil production in Nagylengyel field




Results of CO₂ injection in Nagylengyel field


Cum. oil with primary recovery: 19.1 MMm³
Incremental oil with CO₂: 2.5 MMm³
URF above 55%
Increment 7.5 %



CO₂ gas flooding in Szank-NE and Szank-SE oil fields



- Production started in Szank fields between 1966-1970
- In 1990 water-cut reached 70%, wells produced by beam pumps
- 9 wells were re-completed into injectors and a Sweetening Unit (with amine technology) was built in 1992
- CO₂ content of the associated gas raised up to 80 % in 2002
- The associated gas has been injected back to the aquifer of Szank field since 2003
- ► In the future **corrosion** effect of CO₂ within the well bore must be considered.



CO₂ injection to SZANK-NE SZANK-SE

Process of CO₂ injection

Szank-SE

RF: 36,6 %
Cumulative oil: 10,5
Million bbl
EOR Oil increment:
572 thousand bbl
(RF: +2 %)

Szank-NE

RF: 42,5 %
Cumulative oil: 4,2
Million bbl
EOR Oil increment:
163 thousand bbl
(RF: +1,65 %)

RESULTS and LESSONS LEARNT

Utilization of the synergy between Sweetening Unit and EOR using CO₂ as a by-product of the capturing technology for producing extra oil

Pusztaföldvár CO₂ + WAG + Water Injection

Location of the field

Reservoir parameters



3,3 km² (815,4 acres) Area of reservoirs Type of reservoirs sandstone 1644 ssm (5392 ft) OWC 17,45 MPa (2531 psi) 122 °C (251 °F) 3,5 m (11,5 ft) Net pay 20,6% Porosity Swi 30.0% Permeability 10 mD

Production phases of PF-A-I reservoir:

1960-1972 primary recovery (depletion + water drive)

1973-1983 CO₂ gas injection

1984-2004 WAG and water injection

1984-1989 planning, construction, pressure increasing

1990-1996 WAG injection

1997-2004 water injection

2005- "primary recovery" again




OOIP: 1.06 MMcm




Pusztaföldvár CO₂ + WAG + Water Injection

Oil production (2	10^3m^3)	Rec.F (%)	$Gp = 154,1*10^6 m^3$
Primary oil rec.	293,6	27,6	$Gi = 177,5*10^6 m^3$
CO ₂ injection	62,2	5,8	$Wp = 328,3*10^3 m^3$
WAG+water inj.	56,8	5,3	$Wi = 257,5*10^3 m^3$
Total	412,6	38,7	Pr = 17,4 ⇒ 11,8 MPa




HC injection into light oil reservoir





Results of enhanced recovery of C3-6 components

Oil saturation vs. time by gas injection





Reservoir temperature: 92 C°

400 0 b


Initial reservoir pressure: 169.8 bar


Oil density: 728 kg/m³ Boi: 3.97

OIIP: 2.29 MMm³

Solved GIIP: 1.6 bcm

Cum. Oil with primary recovery: 0.66 MMm³ Cum. Oil on 31 December 2012: 1.4 MMm³ 13% RF increment in C3-C6 components





EOR/IOR in Demjén oil field – Location of the field

Reservoirs of Demjén field:

Demjén-West

Demjén-Pünkösdhegy

Demjén-East

Permeability: 10-100 mD

Average: 80-100 mD

Oil characteristics:

Demjén-West:

Density: 890 kg/m3

Pour point: +35 C°

Viscosity: 49 mPas@29C°

Demjén-East:

Density: 840 kg/m3


Pour point: +5 C°

Viscosity: 5 mPas@38C°

Demjén-Pünkösdhegy:

Mix

High paraffin content






Demjén field – A playground of EOR/IOR experiments

Small scale pilot projects

Demjén-East:

- Micro bacterial (MEOR)
 experiments in Dk-114,-192
 and De-61 wells 1969 1970. Well treatments,
 production increased.
- Air injection (segregation project) in to Dk-83 –
 artificial gas cap, good results.
- Water injection resulted
 317 th m³ incremental oil.




Demjén field – A playground of EOR/IOR experiments

Small scale pilot projects

Demjén-West:

- Steam injection experiment in De-61 well in 1969 – minimal results
- Dry in situ combustion pilot in De-62 well in 1972
- Steam flue gas injection experiment in De-70 in 1989 – good results, incremental oil production.
- "Burn and turn" project on De-70 well in 1991 – good results, 648 tons incremental oil in one year on a small area.




In-situ combustion projects in Demjén-East field


In-situ combustion experiments in Demjén field:

1976: experiment with chemical additive in Demjén-E in a 5-well pattern


1986: wet combustion pilot project in Demjén-E in three 4-well and three 5-well patterns



Temperature raising and results



- 9 injectors were ignited,
- Production grew rapidly but high production rate from the area was short,
- cumulative production was 5-fold of the forecasted (incremental oil 11.2 th m³),
- Combustion front caused damage in production wells,
- Controlling front and flooding was a challenge.



Contents








4. Ongoing EOR activities in the Pannonian basin






Ongoing CO₂ (WAG) project in Ivanić-Žutica fields



CO₂ injection pilot proved the feasibility of the project



CO₂ injection results


- Confirmation of oil displacement by CO₂ in real reservoir environment
- Source of data for fine tuning of simulation models: pilot area and full field
- Practical experience with:
 - CO₂ injection (including safety systems)
 - Oil production after CO₂ breakthrough

CO₂ injection data

- Two slugs
 - one slug is one year
 - in one slug appr. half year CO₂ and half year water injection
- Injection rate:
 45,000 Sm³/day (88 t/day)
- Wellhead: p = 55 bar, T = -20°C
- Downhole: p = 193 bar, T = 60°C
- Slug size: $8.2 \times 10^6 \, \text{Sm}^3 \, (16,000 \, \text{t})$
- No operational problems



EOR – Scope of the project



EOR 1st phase – finalization

- Received (3) use permits for CS Molve, CS Ethane and membrane separator unit on CS Žutica;
- July 18th- September 9th functional testing of CO₂ system (CS Molve, CS Ethane and 11 wells on Ivanić);
- September 30th received approval from Ministry for trial exploitation of the CO₂ system and CO₂ injection into 12 wells;
- October 14th CO₂ injection started into 12 wells in Ivanić;
- Decision for EP Žutica concession approval till the end of September 2015 has been received from Ministry.



Early results of CO₂ injection on oil production



General information on EOR related R&D projects

Projects in field testing phase

- 1. Reducing water inflow in gas wells by injecting metastable micro emulsion
- 2. Application of micro and macro heterogenous gels for fluid flow improvement
- 3. Polymer-surfactant flooding in Algyő field
- 4. Profile control and EOR by applying biotechnology

Supported area

Reservoir technology

Current phase of the projects

Applied research

Strategic objective

Increase recovery factor

TRL classification

In most cases 6







Project 1.

Reducing water inflow in gas wells by injecting metastable micro emulsion

Project description

work out a simple, economical and routinely applicable well service method that is suitable for limiting water production from gas fields and from UGSs

Target of project

average 30-40% less formation water and hereby more HC production 503,200 boe (80 Mm³) gas for Y2015

Milestones in 2014

3 wells were treated. Water production decreased by 30-50%

Activity in 2015

well injection test in further 4 gas wells



Project 2.

Application of micro and macro heterogenous gels for fluid flow improvement



Project description

improve efficiency gels for correcting conditions of fluid flow in porous and fractured reservoirs

Target of project

less formation water production, stop the decreasing oil production rate and sustain the production at the estimated yearly level

Activity in 2014

prepare the selected wells for testing and optimise the applied chemical compound

Activity in 2015

well injection tests in further 4 oil wells

Project 3.

Polymer-surfactant flooding in Algyő field

Project description

using more effective Gemini surfactant with polymers for EOR. Goal of the development is to expand chemical EOR to high temperature reservoirs.

Target of project

successful pilot project in a 2 injectors 5 producers well pattern

Activity in 2014

polymer-surfactant backflow test in well Algyő-758 was completed, preparation for a multi-well pilot.

Activity for 2015

elaborate a multi-well pilot, prepare wells for treatment



Project 4.

Profile control and EOR by applying biotechnology



Project description

Target of project

Activity in 2014

Activity in 2015

Develop bio-tenside, bio-polymers and bio-surfactant biopolymer complex mixtures that can be used for MEOR,

average 20-30 % overall oil production increase

bacteria-bio-surfactant-biopolymer mixture injectivity test in Demjén-W field was completed. Prepare injection wells and the connecting surface technology. microbiological analyse of produced fluids from monitoring wells



Results

Output

Incremental production

in Y2014:

33 470 bbl oil


34 732 boe gas

Expected incremental

production for Y2015:

279 000 bbl oil

518 925 boe gas



and moreover

less water production

less operational and maintenance cost



Contents











5. EOR plans for the future



Polymer-surfactant flooding in Algyő field







Algyő field was discovered in 1965

Algyő is the largest HC accumulation in Hungary: 500 MMbbl OOIP, 4 TCF OGIP


Pannonian deltaic reservoir system

Algyő-2 is one of the 77 reservoirs in the field:

- ► Type of reservoir: sandstone
- ➤ **Porosity:** 23-26%
- Permeability: 200-300 mD
- ► STOOIP: 141 MMbbl
- ► Produced till November 2014: 64,8 MMbbl (46% RF)


.

Polymer-surfactant flooding in Algyő field – Pilot project





Polymer–surfactant flooding in Algyő – Full scale project



EOR/IOR in Demjén oil field – Location of the field

Reservoirs of Demjén field:

Demjén-West

Demjén-Pünkösdhegy

Demjén-East

Permeability: 10-100 mD

Average: 80-100 mD

Oil characteristics:

Demjén-West:

Density: 890 kg/m3

Pour point: +35 C°

Viscosity: 49 mPas@29C°

Demjén-East:

Density: 840 kg/m3


Pour point: +5 C°

Viscosity: 5 mPas@38C°

Demjén-Pünkösdhegy:

Mix

High paraffin content




In-situ combustion experiments in Demjén field:

1972: first experiment in Demjén-W in a 5-well pattern

1976: experiment with chemical additive in Demjén-E in a 5-well pattern

1986: wet combustion pilot project in Demjén-E in three 4-well and three 5-





Complex EOR/IOR program design for Demjén field




Cautious estimations regarding results of IOR/EOR applications:

- Water + new wells: 166 thcm
- Water + new wells + perforation modifications:

342 thcm

Further incremental oil production up to: 1 178 thcm



Incentives for production enhancements

Hungary: Mining Act (Bt.)

- **Bt.20§(5): royalty is 0%** for the volume of **HC produced** with "enhancement technologies",
- Bt.49§ 25.: "enhancement technologies" means those applications what increases the HC production after primary and secondary recovery,
- Bt. Enacting Clauses 4§(10)-(10a): a technology can be considered to "enhancement technology" if its effect on reserve increase is proven.

UK: Oil and gas taxation

- Types of field allowances: Small Field (SFA) from 2009, Ultra Heavy Oil Field (UHO) from 2009, Brown-field (BFA) from 2012,
- Applicable against 32% supplementary tax,
- Maximum **UHO allowance** per field **800 GBPmIn** reduces tax paid up to **256 GBPmIn**,
- Maximum BFA per field 250-500 GBPmIn reduces tax paid up to 80-160 GBPmIn.

Other tax and/or royalty allowances exist in Canada, Mexico, Russia, etc.





Contents














Conclusions








- ► A good farmer cares about its sheep strategy for production portfolio management is crucial to optimize the performance.
- Regular EOR/IOR screening of assets is important to know the actual future potential of our producing assets.
- ▶ Do not forget the past experiences either positive or negative – use it for future development.
- ▶ R&D is an important tool to develop and implement new technologies for higher production efficiency and recovery, for future oil and gas.
- ► Speed of transforming idea to project implementation can be critical in case of an old field.

Do not let to die your field...



Thank you for your kind attention!













